

# CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-000762-01

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product(s)

Product(s):

Building hardware - Controlled door closing devices - Requirements and test methods (refer to attached appendix for details and conditions)

Placed on the market

EURO ART (UK) Ltd.

under the name or trade mark of:

69 Staverton Road, London, NW2 5HA, United Kingdom.

and produced in the manufacturing plant(s):

SG-15472

Intended use:

On fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors)

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s):

EN 1154:1996/A1:2002/AC:2006

Under System 1 for the performances set out in this certificate are applied and that the performance of the construction product fulfils all the prescribed requirements for these performances.

This certificate replaces **0359-CPR-000762-01** first issued on **2019-06-05** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performances of the declared essential characteristics, do not change, and the construction product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the product certification body.

CE

The issued document and statement(s) herein makes reference only to a presumption of conformity in accordance with the CPR Regulations EU 305/2011 (as amended). However, it is the manufacturer's or their authorised representative's sole responsibility to affix the CE logo and, by doing so, confirms full compliance and conformity to all other European mandatory directives and regulations that may also apply.

Signature:

Date:

2019-10-30

4

Issu

01

Name:

Dipl.-Ing. Roland Heine

Position:

**Certification Manager** 

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de

2202 Page 1 of 3 RET\_FII\_NR\_OP\_23v2a



# CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-000762-01

### **APPENDIX TO: Certificate of Constancy of Performance**

Brand:

**EUROART** 

Model Ref:

DC1024

#### Table A1. Product classification from EURO ART (UK) Ltd.

Installation Position	Installation Type	Product Classification					
EN 2	Standard arm	4	8	2	0	1	4
EN 3	Standard arm and parallel arm	4	8	3	1 a	1	4
EN 4		4	8	4	1 a	1	4

#### Table A2. Mechanical test reports & Product classification for Door Closer from EURO ART (UK) Ltd. b

180131127GZU-001	Installation Type	Product Classification					
	Standard arm	4	8	4	1ª	1	4
	Standard arm	4	8	2	1	1	4
	Parallel arm	4	8	3	1 ª	1	4

#### Table A3. Fire test report(s) for Door Closer from EURO ART (UK) Ltd. b

Test Report	Installation Type	Test Method	Fire resistance (minutes)		
			E - Integrity	I - Insulation	
180511007SHF-BP-2	Parallel arm	EN 1634-1:2014	75	75	

#### Notes.

- a. Digit 4 grade "1" was based on the test result from fire resistance test (refer to Table A3).
- b. The door closer shall be installed in accordance with the installation instructions for the product(s).

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen

Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de



## **CERTIFICATE OF CONSTANCY OF PERFORMANCE**

0905-CPR-000762-01

### **APPENDIX TO: Certificate of Constancy of Performance**

Table A3. EN 1154 Annex ZA Related Information for Door Closer from EURO ART (UK) Ltd.

Product:	Controlled door closing devices DC1024			
Intended use:	On fire and smoke compartmentation doors (to fulfil the self-closing requirementation doors)			
Requirement/ characteristic	Standard clause	Result Summary		
Self-closing	General (5.2.1)	Grade 4 (closing doors from at least 125° open)		
	Closing moment (5.2.3)	Power size 2 to 4		
	Opening moment (5.2.4)	Power size 2 to 4		
	Efficiency (5.2.5)	Power size 2: More than 50% Power size 4: More than 60%		
	Closing time (5.2.6)	Pass		
	Angles of operation (5.2.7)	Grade 4, 125°		
	Overload performance (5.2.8)	Pass		
	Temperature dependence (5.2.9)	Pass ( -15°C to +40°C)		
	Fluid leakage (5.2.10)	Pass		
	Damage (5.2.11)	Pass		
	Latch control (5.2.12)	Pass		
	Backcheck (5.2.13)	Pass		
	Delayed closing (5.2.14)	NPD		
	Adjustable closing force (5.2.15)	NPD		
	Zero position (5.2.16)	NPD		
	Fire/smoke door suitability (5.2.18), Annex A	Grade 1, Suitable for use on fire/smoke doors (refer to Table A3).		
Durability of	Durability (5.2.2)	500,000 test cycles		
self-closing	Corrosion resistance (5.2.2 5.2.17.1, 5.2.17.2)	Grade 4, Neutral Salt Spray (NSS) for 240 hours		
Dangerous substances	See Clause ZA.3	No dangerous substances declared for this product/intended use		

#### **END OF DOCUMENT**

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen

02202